

Intelligent EV AC Charger 11kW

EMN011AC1BA



3 Phases



Type 2 Plug



LAN / WLAN / RS485



RFID



Fuse



LCD Display



IP65 & IK10

Produkt-Info / Product info



With this **3-phase EM2GO EV charging station with 11 kW power and 7.5 meter long Type 2 charging cable**, you can charge your e-vehicles safely and quickly. The EM2GO Wallbox with **intelligent control** has a variety of **communication interfaces** for backend control. Multiple wallboxes can be interconnected with **local load management** to share available power. The wallbox has an **RFID card reader**.

The built-in **all-current sensitive residual current unit (RCMU)** protects against fault currents during a charging process. The **4.3 inch color display** informs you about the current state of charge, charge voltage, current and power during the charging process. An **LED band** indicates the status of the wallbox and informs about the proper charging process.

The EM2GO EV charging station is equipped with **intelligent electronics**. So your vehicle is **well protected** against over/under voltage, fault currents, short circuits and high temperatures. The integrated **safety lock** on the back of the wallbox allows easy installation and protects against theft.

The EV charging station is delivered together with the **becharged dashboard**. After registration, the charging station can be conveniently controlled and managed via the central dashboard, **including APP**. The becharged dashboard includes the overview of the charging station/user and the **graphical evaluations of the charging processes**. Transactions made can be exported for reporting purposes. Simple load management allows to limit the amount of electricity used by the charging station. Additional features, such as billing services can be enabled through value-added services in the becharged dashboard.

Technische Daten:

- Operating voltage: 400V AC $\pm 10\%$, 50-60 Hz
- Operating current: 16 Amps
- Max. Output power: 1-phase 16A up to 3.7kW / 2-phase 16A up to 7.4kW / 3-phase 16A up to 11kW
- Charging connection: Type 2, cable length 7.5m
- Local load management
- Display: 4.3 inch LCD screen, LED band
- Phase mode: 3 phases + N + PE
- Interfaces: RS-485, Ethernet (RJ-45), WLAN (2.4GHz)
- Backend connection: OCPP standard 1.6-J (WS & WSS)
- ModBus TCP support
- Integrated RFID card reader
- Safety: All-current sensitive residual current unit (RCMU), emergency stop button, over temperature, over/under voltage, over current, grounding protection
- Operating temperature: -30 to +55 °C
- Housing: IP65 & IK10, splash-proof
- Dimensions: 435 x 270 x 140 (H×W×D)
- Weight: 10 kg

Art.Nr: EMN011AC1BA

EAN: 4024559262487

Technische Änderungen vorbehalten / Improvement and changes of the technical specifications and other data's could be made without prior notice